



QUADEX QUAD-PLUG

**FAST SETTING
CEMENTITIOUS WATERSTOP**

DESCRIPTION:

Quadex Quad-Plug is a blend of special cements and admixtures which are designed to instantly stop running water or seepage in all types of concrete and masonry structures.

RECOMMENDED FOR:

Sewer Pipes and Manholes
Concrete Tanks
Elevator Pits
Cisterns
Basements
Concrete & Masonry Walls

FEATURES AND BENEFITS:

Stops running water immediately
Non-Shrink, expands as it sets
Contains no calcium chloride
Non-Metallic
Sulfate resistant
Easily applied
No Mixing

TYPICAL PERFORMANCE DATA:

Compressive Strength
STRENGTH – PSI (MPa)
(ASTM C109)

30 min. 1850 psi
28-day 5800 psi
>9000

Bond Strength
(ASTM C321)

30 min. 50 psi
1 day 85 psi

PACKAGING:

Quadex Quad-Plug is supplied in a 50 lb. plastic pail.

YIELD:

Quadex Quad-Plug will yield approximately .45 cu. ft. (787 cu. in.) per pail.

APPLICATION INFORMATION:

TO SEAL RUNNING WATER OR LEAKS:

Prepare crack or hole by chipping out loose material to a minimum depth and width of 3 / 4 ". Using a rubber gloved hand, place a generous amount of dry **Quadex Quad-Plug** with a smooth fast motion to active leak, maintaining external pressure for 30 seconds. Repeat until leak stops.

WARRANTY:

Quadex warrants its products to be free of defects in material and workmanship. **Quadex** will replace any product proved to be defective when applied in accordance with manufacturer's instructions. **Quadex's** obligation shall be limited solely to such replacement. There are no other warranties by **Quadex** expressed or implied.

PRECAUTIONS:

Avoid eye contact or prolonged contact with skin. Wash thoroughly after use. Persons using **Quadex Quad-Plug** should wear necessary eye protection, dusk mask and rubber gloves. Read all product labels and technical literature.